
System Zero®













		LENGTH	DI.	V	1/4"	1/2"	3/4"	1"	DRIVER
DIA	DIAMETER		Dk	K	6mm	13mm	19mm	25mm	SIZE
N	o. 4	2.9mm	5.3	2.1	SZS04B-Z	SZS04D-Z			SZ3
N	o. 6	3.5mm	5.3	2.1	SZS06B-Z	SZS06D-Z	SZS06F-Z	SZS06G-Z	SZ3
N	o. 8	4.2mm	7.2	2.6		SZS08D-Z	SZS08F-Z	SZS08G-Z	SZ4

Material: Steel

Heat Treatment: Case Hardened

Finish: Zinc Plated

ZINC

Zinc is an electrodeposited lightweight plating that gives a sacrificial protection to underlying substrates (carbon steel).

This method lays a thin layer of zinc over the surface meaning the zinc plating would corrode in preference to the substrate and therefore protecting the covered steel product.

Salt Spray (hrs)

Thickness and Passivation White Rust Red Rust 3μ CR3+ 24 72

Installation: Extra Long (75mm) insert bit

Removal: 2-Way Removable Screw





Every effort has been made to ensure the accuracy of information provided in this catalogue. Hafren Fasteners cannot warrant the information however, expressly or implied, and any liability arising from it is expressly excluded. Customers must satisfy themselves as to the suitability of products and the technical information relating to them, and it is recommended that you conduct your own tests to establish suitability. All sizes shown are in mm without min and max tolerances and are guide sizes. Hafren Fasteners reserve the right to change/alter sizes without notice. This does not effect your statutory rights.